



# EET5KPro/6KPro/8K/10K/12K/15K/18K/20K-M1

## Three Phase On-grid Inverter



### Higher Yield

98.8% max efficiency;  
3 MPPTs



### Higher Quality

IP66 ingress protection; Efficient heat dissipation;  
Uvioresistant; Corrosion resistant



### Communications

Wifi, 4G, GPRS, Bluetooth, RS485;  
Remote monitoring



### Compatibility

AC output voltage 180 V to 300 V adjustable, compatible  
with the grids of most countries;  
Higher DC max input voltage and current



### Easy to use

Light weigh and smaller size;  
Easy to install



### Safety

Enhanced safety with hardware & software protection  
Thunder-proof and low radiance

Model	EET5KPro-M1	EET6KPro-M1	EET8K-M1	EET10K-M1
<b>DC Input Data</b>				
Recommended max. PV power(KW)	7.5	9	12	15
Max. input voltage(V)	1100			
MPPT voltage range(V)	100~1080			
Max. input current(A)	18/18/18	18/18/18	18/18/18	18/18/36
Max. short circuit current(A)	22/22/22	22/22/22	22/22/22	22/22/44
MPPT number	3			
String number per MPPT	1/1/1	1/1/1	1/1/1	1/1/2
<b>AC output Data</b>				
Rated output power(KW)	5	6	8	10
Rated/Max. apparent output power(KVA)	5/5	6/6	8/8	10/10
Max. active power(KW)	5	6	8	10
Rated grid output current(A)	7.25	8.7	11.6	14.5
Max. output current(A)	7.25	8.7	11.6	14.5
Rated grid voltage/range(V) (3P/N/PE)	220/380, 230/400, 240/415, 312~520			
Rated grid frequency(Hz)	50/60			
Power Factor	>0.99, (-0.8 to +0.8 adjustable)			
THDi	<3%			
<b>Efficiency</b>				
Max. efficiency	98.80%			
EU efficiency	98.30%			
<b>Protection</b>				
Ground fault monitoring	Yes			
Output over voltage protection	Yes			
Anti-islanding protection	Yes			
Integrated AFCI	Optional			
DC reverse-polarity protection	Yes			
Over voltage category	AC ClassIII/PV ClassII			
<b>General Data</b>				
Dimension(mm) (W*H*D)	411*401*162			
Shell material	Aluminium alloy			
Noise Emission(dBA)	≤20			
Weight(Kg)	15			
Operating ambient temperature range	-25~60 C			
Topology	Transformerless			
Ingress protection	IP66			
Cooling concept	Natural convection			
Max. operation altitude(m)	3000			
Grid connection standard	AS/NZS 4777.2:2020, EN50549-1:2019, G98:2021, G99:2021, NC RFG, PTPiREE, ABNT NBR 16149, ABNT NBR 16150, VDE-AR-N 4105, CEI0-21, RD1699			
Safety/EMC standard	IEC-62109-1/-2, IEC-62477-1/-2, IEC-61000-6-1/-2/-3, NB/T32004			
Country of manufacturing	China			
DC connection	MC4/D4			
Communications	Wifi(2.4G), 4G, GPRS, Bluetooth, RS485			

Model	EET12K-M1	EET15K-M1	EET18K-M1	EET20K-M1
<b>DC Input Data</b>				
Recommended max. PV power(KW)	18	22.5	27	30
Max. input voltage(V)	1100			
MPPT voltage range(V)	100~1080			
Max. input current(A)	18/18/36	18/18/36	18/18/36	18/18/36
Max. short circuit current(A)	22/22/44	22/22/44	22/22/44	22/22/44
MPPT number	3			
String number per MPPT	1/1/2	1/1/2	1/1/2	1/1/2
<b>AC output Data</b>				
Rated output power(KW)	12	15	18	20
Rated/Max. apparent output power(KVA)	12/12	15/15	18/18	20/20
Max. active power(KW)	12	15	18	20
Rated grid output current(A)	17.4	21.7	26.1	29
Max. output current(A)	17.4	21.7	26.1	29
Rated grid voltage/range(V) (3P/N/PE)	220/380, 230/400, 240/415, 312~520			
Rated grid frequency(Hz)	50/60			
Power Factor	>0.99, (-0.8 to +0.8 adjustable)			
THDi	< 3%			
<b>Efficiency</b>				
Max. efficiency	98.80%			
EU efficiency	98.30%			
<b>Protection</b>				
Ground fault monitoring	Yes			
Output over voltage protection	Yes			
Anti-islanding protection	Yes			
Integrated AFCI	Optional			
DC reverse-polarity protection	Yes			
Over voltage category	AC ClassIII/PV ClassII			
<b>General Data</b>				
Dimension(mm) (W*H*D)	411*401*162			
Shell material	Aluminium alloy			
Noise Emission(dBA)	≤40			
Weight(Kg)	15.2			
Operating ambient temperature range	-25~60 ℃			
Topology	Transformerless			
Ingress protection	IP66			
Cooling concept	Smart fan&Natural convection			
Max. operation altitude(m)	3000			
Grid connection standard	AS/NZS 4777.2:2020, EN50549-1:2019, G98:2021, G99:2021, NC RFG, PTPiREE, ABNT NBR 16149, ABNT NBR 16150, VDE-AR-N 4105, CEI0-21, RD1699			
Safety/EMC standard	IEC-62109-1/-2, IEC-62477-1/-2, IEC-61000-6-1/-2/-3, NB/T32004			
Country of manufacturing	China			
DC connection	MC4/D4			
Communications	Wifi(2.4G), 4G, GPRS, Bluetooth, RS485			